



SiSiB® VT5545 SILANE


- 1 -

INTRODUCTION


SiSiB® VT5545 is a colorless to yellowish liquid, composite of 55% SiSiB® PC7500 (VOS) and 45% Tetra(methylethylketoxime)silane (TOS).

CHEMICAL STRUCTURE

Vinyltris(methylethylketoxime)silane: 55%



Tetra(methylethylketoxime)silane: 45%



APPLICATIONS

It is used as a raw material (crosslinker) for neutral crosslinking RTV-1 sealants.

PACKING AND STORAGE

SiSiB® VT5545 is supplied in 190Kg steel drum or 950Kg IBC container.

In the unopened original container SiSiB® VT5545 has a shelf life of one year in a dry and cool place.

NOTES

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

Power Chemical
ISO9001 ISO14001 certificated

Copyright© 2009 Power Chemical Corporation Ltd.
SiSiB® is a registered trademark of PCC. For more knowledge regarding organosilanes, you may visit www.SiSiB.com or www.PCC.asia



SiSiB[®] VT5545 SILANE

- 2 -

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability. We disclaim liability for any incidental or consequential damages.

Please send all technical questions concerning quality and product safety to: silanes@SiSiB.com.

Power Chemical
ISO9001 ISO14001 certificated

Copyright© 2009 Power Chemical Corporation Ltd.
SiSiB[®] is a registered trademark of PCC. For more knowledge regarding organosilanes, you may visit www.SiSiB.com or www.PCC.asia